



SCHEMATIC



P.C.B.LAYOUT

RoHS Compliance





NO.	PART	MATERIAL	QTY	REMARKS	NO.	PART	MATERIAL	QTY	REMARKS
5	CONTACT	CuBe	2	Ag PLATED	6	SPRING PLATE	S U S	1	
3	TERMINAL	BRASS	6	Ag PLATED	4	COVER BOARD	S U S	1	
1	FRAME	NYLON 46	1		2	KNOB	NYLON 46	1	TG 1-3

ISSUED	SPECIFICATION	TITLE: MINIATURE SLIDE SWITCH (2P2T)			
	RATING: DC 12V 0.1A	MODEL NO: MSS-22C02			
	CONTACT RESISTANCE: 70mΩ max.				
	INSULATION RESISTANCE: 100MΩ AT 500V DC	TOLERANCE	UNIT: MM	DWN.	
	WITHSTAND VOLTAGE: AC 100V for 1 minute	UP TO 1.0:±0.1	SCALE: 8:1	CHK'D.	
	OPERATION FORCE: REFER ATTACH SPECIFICATION	1.0 TO 10.0:±0.2	VERSION: 04		
	SWITCHING LIFE: 10K cycles min.	OVER 10.0:±0.3	DRWG NO:	APPD.	