



RoHS  
Compliance



7	BALL	STEEL	2					
5	CONTACT	P B S	8	Ag PLATED	6	SPRING	STEEL WIRE	1
3	TERMINAL	BRASS	48	Ag PLATED	4	TERMINAL BASE	PHENOL RESIN	1
1	FRAME	S P C C	1	Ni PLATED	2	KNOB	P O M	1
NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY
								REMARKS

ISSUED

SPECIFICATION

TITLE: SLIDE SWITCH (8P5T)



RATING: DC 30V 0.5A  
 CONTACT RESISTANCE: 30mΩ max.  
 INSULATION RESISTANCE: 500MΩ at 500V DC  
 WITHSTAND VOLTAGE: AC 500V for 1 minute  
 OPERATION FORCE: REFER ATTACH SPECIFICATION  
 SWITCHING LIFE: 10K cycles min.

MODEL NO: SS-85D01 ( G )

TOLERANCE	UNIT: MM	DWN.	<i>hw</i>
UP TO 1.0: ±0.1	SCALE: 2:1	CHK'D.	<i>hw</i>
1.0 TO 10.0: ±0.2	VERSION: 1	APPD.	<i>hw</i>
OVER 10.0: ±0.3	DRWG NO:		