







PCB LAYOUT
(Bottom View)

SPECIFICATION :

1. Electrical Char.

Insulation Resistance : 500M-Ohm Min.
Contact Resistance : 20milli-Ohm Max.
Rating Current : 1.5A Max.
Rating Voltage : 120V AC
Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

Housing : PBT Glass Filled (UL 94V-0)
Color : Black Color
Spring Wire : 0.45mm Dia. Phosphor Bronze
Gold Plating Over Nickel
Temperature Range : - 25 /+90 Deg C

AJ-001-4-A-X

A=4p4c

Gold
plated

1=15u , 3=50u
2=30u , 4= 6 u

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
THIRD ANGLE PROJECTION	LINEAR $\frac{MM}{INCH}$	00 ± 0.01 000 ± 0.005 0000 ± 0.002	00 ± 0.25 000 ± 0.13 0000 ± 0.05	CK'D Johnn	JUL-29 '04
$\frac{MM}{INCH}$	ANGLE $\pm 30'$	RADIL	$+0.45$ -0.15	APP'D Billy	JUL-29 '04

DWG. NO.
AS001001

TITLE

RJ11 BOTTOM ENTRY PCB JACK
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
AJ-001-4-A-X

SCALE SIZE DWG. NO.9622-4 SERIES