







**PCB Layout
(Top View)**



SPECIFICATION :

1. Electrical Char.

Insulation Resistance : 500M-Ohm Min.

Contact Resistance : 20milli-Ohm Max.

Rating Current : 1.5A Max.

Rating Voltage : 120V AC

Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

Housing : PBT Glass Filled (UL 94V-0)

Color : Black Color

Spring Wire : 0.45mm Dia. Phosphor Bronze

Gold Plating Over Nickel

Temperature Range : - 25 /+90 Deg C

Durability : 500 Mating cycles Min.

AJ-019SH-6-X-X-B1-N1

B=6p2c, C=6p4c
D=6p6c

Gold plated 1=15u, 3=50u
2=30u, 4= 6 u

DWG. NO.

AS019022

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
 THIRD ANGLE PROJECTION	LINEAR $\frac{MM}{INCH}$	00±0.01 000±0.005 0000±0.002	00±0.25 000±0.13 0000±0.05	Steven	JAN-12 '05
		ANGLE +0°30'	RADIL	Johnn	JAN-12 '05
MM INCH				Billy	JAN-12 '05

TITLE

VERY LOW PROFILE PCB SHIELDED JACK
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
AJ-019SH-6-X-X-B1-N1

SCALE SIZE DWG. NO. 9695S SERIES