

REV	DATE	MODIFICATION	DRAWN
	11/05/05		

SPECIFICATIONS
1. ELECTRICAL:
UL APPLICATIONS: 250 VOLTS AC MAX. AT 2 AMPS.
DIELECTRIC WITHSTANDING VOLTAGE: 500 VOLTS AC.
INSULATION RESISTANCE: 100 MΩ.
TERMINATION: RESISTANCE 20mΩ MAX AFTER ENVIRONMENTAL TESTING.

2. MECHANICAL:
CABLE-TO-PLUG TENSILE STRENGTH: 19.6N/PCS MIN.
DURABILITY: 200 MATING CYCLES.
3. MATERIAL & FINISH:
HOUSING: POLYCARBONATE, UL94V-0 OR UL94V-2.
COLOR: TRANSPARENT OR OTHER COLOR ARE AVAILABLE.
CONTACT BLADE: PHOSPHOR BRONZE.
CONDUCTOR: STRANDED & SOLID WIRE, 24AWG, 26 AWG.
GOLD PLATING: 3u"~50u" ARE AVAILABLE.

规范

1. 电器:

UL应用最大250VOLTS AC.
介质耐电压伏特数:500VOLTS AC.
绝缘阻抗:100百万欧姆。
终端阻抗:在环境测试后最大可承受20微欧姆终端阻抗。




2. 机构

拉力测试:至少19.6N/PCS.
耐力测试:至少200次之插拔测试。
3. 材质表面处理
塑胶壳:聚碳酸脂,UL-94V-0 or UL94V-2.
颜色:透明,或者其他颜色亦可。
金片:磷铜片。
导体:多股线&单股线,24AWG,26AWG.
镀金厚度:3u"~50u",皆可提供。

客户用产品图

Type	E-03	B-03	Y-03	Z-03
Drawing				
Mark				

BLADE:



DIMENSION IN mm (inch)	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL	图号
.XX±0.10	.XX°±2°	PC	DWG NO.
.X°±5°		名称	PLUG-10P10C SHIELDED
.XX°±2°		描述	
审核	核对	制图	比例
APPROVAL	CHECKED	Lucia	2/1
		角法	张数
		PROJ.	更改
		REV	A