



- NOTES:
- MATERIALS
 - Insulator: PC
 - Contact: Brass
 - Contact Plating: TINK(100~120U') Plated
 - SPECIFICATIONS
 - Current Rating: 3 Amp
 - Contact Resistance: 25mΩ Max
 - Dielectric Strength: 1000V AC for one minute
 - Insulator Resistance: 1000MΩ Min.(at 500V DC)
 - Operation Temperature: -55°C to +105°C

REV.	NOTES	DATE
A	RELEASED	2006/03/03
B	Ø 1.10 改爲Ø 1.30±0.05	2006/09/08
C	增加尺寸,修改圖面	2006/09/14
D	AMEND NOTES:16.90變更爲16.60;10.00變更爲10.10	2006/09/14
E	4.0±0.05變更爲4.0	2006/12/29

DIMENSIONS TOLERANCE		圖名 (NAME)	
METRIC	0 = ± 3	料號 (PART NUMBER)	ASC+0360-40C
	.00 = ± .20	圖號 (DRAW NUMBER)	RASC036040C
	.0000 = ± .XXX	圖檔 (FILE NAME .DWG)	E:GCT/A/SC/03
	ANG. = ± 2'	比例 (SCALE)	1/1
		圖紙 (SHEET)	A4
		頁次 (SHEET)	1
		版本 (REV.)	E

BASE LINE

PCB LAYOUT

90度母座有柱有圓孔錫 PC 無毒