



MATERIALS AND FINISH

SHELL : STEEL MATERIAL, NICKEL FINISHED
DIMPLES ON PLUG ONLY

INSULATOR : PBT THERMOPLASTIC, 30% GLASS
FILLED, UL 94V-0 RATED, BLACK COLOR

CONTACT MATERIAL: BRASS

CONTACT FINISH : SELECTIVE GOLD FLASHED

GROUNDING BRACKET : BRASS MATERIAL, TIN FINISHED

RIVETED INSERT : BRASS MATERIAL , NICKEL FINISHED

ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS

CONTACT RESISTANCE : 30 MILLIOHMS MAX.

DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.

INSULATION RESISTANCE : 5000 MEGAOHMS MIN.

TEMPERATURE RATING : -55°C ~ +105°C

| | | |
|--------------------------|--------------|------------|
| Drawn by | jankey | 2007.11.07 |
| Designed by | jankey | 2007.11.07 |
| Approved by | jankey | 2007.11.07 |
| | Sheet 1 of 1 | Code 000 |
| Dimensions in mm(inches) | | Scale 1:1 |
| Tolerances on:XX±-0.13 | | Angles±-2° |

9pin 180°

Ver A0 Part No: 1151A-009-101-00