



P.C.B Layout

Specifications
 Current ratings: 0.5A
 Voltage rating: 150V AC
 Operating Temperature Range: -45°C T0 +125°C
 Operating Humidity Range: 40% T0 80%
 Storage Temperature Range: -10°C T0 +60°C
 Storage Humidity Range: 40% T0 70%

MATERIAL
 Insulator: PA46 30%G. F. UL94V-0
 Terminal: Phos. Bronze, Tin plated 100u"

POS	A	B	C	D
9	8.30	3.00	4.00	7.10
11	9.30	4.00	5.00	8.10
13	10.30	5.00	6.00	9.10
15	11.30	6.00	7.00	10.10
17	12.30	7.00	8.00	11.10
19	13.30	8.00	9.00	12.10
21	14.30	9.00	10.00	13.10
23	15.30	10.00	11.00	14.10
25	16.30	11.00	12.00	15.10
31	19.30	14.00	15.00	18.10
41	24.30	19.00	20.00	23.10
51	29.30	24.00	25.00	28.10

2	DF9-SMT-ST (T100)	X	PCS	HX6	用量	单位	代码
1	DF9-SMT-B-XS 定位柱	1	PCS	JLC			
品名规格							

未注公差:
 GENERAL TOLERANCES

X. ± 0.5
X.X ± 0.3
X.XX ± 0.2
X.XXX ± 0.05

DRAWN	DATE	
LXZ	2006.07.13	
CHECKED	DATE	
TITLE: DF9-SMT-XS (T100) 有定位柱		
APPROVED	DATE	
PART NO.		/
CLIENT P/N		/
UNIT: mm	SCALE: Free	REV. A
FILE NO.: NS-DF9-A00011		GC