



REFERENCE PCB LAYOUT

REV	MODIFICATION	DATE	DRAW

Specification:

Withstanding Voltage: 500VAC Max with 1 Minute
 Insulation Resistance: 1000MΩ min
 Ratings
 Voltage : 100 Volts DC, AC(rms) 100 Volts (per pin)
 Current : 0.5 Amperes DC (per pin)
 Operating Temperature : -25C~+85C
 Contact Retention Force: 100 Gram(0.98N) min
 Insertion Force: 15N Max
 Separation Force: 15N Max
 Insertion Cycles: 5000 Times

Ordering Information:

TFDMF-108 XX BT00
 05-- 5u" Gold Plating
 10-- 10u" Gold Plating
 15-- 15u" Gold Plating

DIMENSION IN mm [inch]		PROD. SPEC.	TITLE		CUSTOMER DRAWING	
TOLERANCE UNLESS OTHERWISE SPECIFIED		PKG. SPEC.	TRANS FLASH CARD CONNECTOR HINGE TYPE		DRAWING	
X±0.05	X'±	APPROVE	FILE NO.	DWG NO. TFDMF-108XXBT00	PROJ.	SHEET 1
.XX±0.05	.X'±	CHECK	SIZE A4	SCALE 3:1	REV	A
.XXX±0.05	.XX'±	DRAW	1			

